

减速电机基本性能参数										文件编号		TB-Y-20221001-32(A/0)	
电机型号		4RK25/30/40CC		电机极数		4P							
额定电压		AC220V(单相)		空载转速		1480r/min							
额定功率		25/30/40W		工作制		S1							
额定电流		0.3/0.35/0.4A		绝缘电阻		>50MΩ							
额定转速		1250r/min		电气强度		1500V/min							
额定转矩		0.19/0.23/0.3Nm		绝缘等级		B							
额定频率		50Hz		防护等级		IP44							
空载电流		—											
齿轮箱规格		80GZ5-240RT											
噪声		<60dB(L=1m)											
使用环境温度		-10℃~40℃											
湿度		相对湿度90%以下											
减速比		减速级数		与电机 旋转方向		传动效率		输出转矩N·m(允许最大输出扭矩8N·m)					
5		3		相反		73%		25W		30W		40W	
6								0.69		0.83		1.11	
7.5								0.83		1.00		1.33	
9								1.04		1.25		1.67	
10								1.25		1.50		2.00	
12.5								1.39		1.67		2.23	
15								1.74		2.09		2.78	
18								2.09		2.50		3.34	
20								2.50		3.01		4.01	
25								2.78		3.34		4.46	
30								3.48		4.18		5.57	
36								4.18		5.01		6.69	
40								5.01		6.02		8.03(8)	
45								5.57		6.69		8.92(8)	
50								6.27		7.52		10.03(8)	
60								6.97		8.36(8)		11.55(8)	
75								8.36(8)		10.03(8)		13.38(8)	
90								9.45(8)		11.34(8)		15.12(8)	
100								11.34(8)		13.61(8)		18.15(8)	
120								12.60(8)		15.12(8)		20.16(8)	
150								15.12(8)		18.15(8)		24.20(8)	
180								18.90(8)		22.69(8)		30.25(8)	
200								22.69(8)		27.22(8)		36.30(8)	
240								25.21(8)		30.25(8)		40.33(8)	
								30.25(8)		36.30(8)		48.40(8)	
客户名称													

版本号			
借通用件登记			
旧底图总号			
底图总号			
签字			
日期			

电机接线图			

外形图		台邦电机工业集团有限公司	
设计		更改文件号	
校对		标准化	
审核		审定	
工艺		日期	
图样标记		重量	
		比例	
		1:2	
共 1 页		第 1 页	

请确认		客户签名		日期	
		产品编码			

微型交流直角减速电机		4RK25/30/40CC/80GZ5~240RT	
------------	--	---------------------------	--