

减速电机基本性能参数										文件编号		TB-Y-20221001-48(A/0)	
电机型号		5RK60CC-F		电机极数		4P							
额定电压	AC220V(单相)		电机转速	14.80rpm									
额定功率	60W		空载转速	14.80rpm									
额定电流	1.1A		工作制	S1									
额定转速	1300rpm		绝缘电阻	>50MΩ									
额定转矩	0.44Nm		电气强度	1500V/min									
额定频率	50Hz		绝缘等级	B									
空载电流	—		防护等级	IP44									
齿轮箱规格	90G25-180RT												
噪声	<60dB(L=1m)												
使用环境温度	-10℃-40℃												
湿度	相对湿度90%以下												
减速比	与电机	传动	输出转矩Nm(允许最大输出扭矩20Nm)										
5	减速级数	旋转方向	效率										
6			60W										
7.5			16										
9			19										
10			2.41										
12.5			2.89										
15			3.21										
18			4.02										
20			4.82										
25			5.79										
30			6.43										
36			8.04										
40			9.65										
50			11.58										
60			12.87										
75			16.08										
90			17.45										
100			21.81(20)										
120			26.18(20)										
150			29.09(20)										
180			34.90(20)										
			4.363(20)										
			52.36(20)										
客户名称				请确认									
版本号				客户签名									
借通用件登记				日期									
旧底图总号				产品编码									
底图总号				外形图									
签字				图样标记									
日期				重量									
				比例									
				台邦电机工业集团有限公司									
				微型交流直角减速电机									
				5RK60CC-F/90G25~180RT									
				共1页 第1页									

电机接线图			

外形图			