

文件编号										TB·Y-20221001-52(A/0)									
减速电机基本性能参数																			
电机型号				5RK60CC·F															
额定电压				AC220V(单相)				电机极数				4P							
额定功率				60W				空载转速				14.80rpm							
额定电流				1.1A				工作制				S1							
额定转速				1300rpm				绝缘电阻				>50MΩ							
额定转矩				0.44Nm				电气强度				1500V/min							
额定频率				50Hz				绝缘等级				B							
空载电流				—				防护等级				IP44							
齿轮箱规格				90GZ5-180RC															
噪声				<60dB(L=1m)															
使用环境温度				-10℃~40℃															
湿度				相对湿度90%以下															
减速比		减速级数		与电机 旋转方向		传动 效率		输出转矩N·m(允许最大输出扭矩20N·m)											
5		3		相反		73%		60W											
6								16											
7.5								19											
9								2.41											
10								2.89											
12.5								3.21											
15								4.02											
18								4.82											
20								5.79											
25								4		相同		66%		6.43					
30		8.04																	
36		9.65																	
40		11.58																	
50		12.87																	
60		16.08																	
75		17.45																	
90		21.81(20)																	
100		26.18(20)																	
120		29.09(20)																	
150		34.90(20)																	
180		43.63(20)																	
		52.36(20)																	
客户名称																			
版本号																			
借通/用件登记 旧底图总号																			
底图总号																			
签字																			
日期																			
电机接线图																			

外形图									
请确认									
客户签名					日期				
产品编码									
台邦电机工业集团有限公司									
微型交流直角减速电机									
5RK60CC·F/90GZ5~180RC									

标记	次数	更改文件号	签字	日期	图样标记			重量	比例
设计									1:3
校对									
审核									
工艺									
					共 1 页			第 1 页	